













Robust and professional: • Painted steel structure with stainless steel panels • Two 300mm wheels • Two castors, one with brake • Three ceramic piston pump with connecting rod operation • 1450 rpm heavy-duty electric motor • Motor-pump elastic coupling • Electrical box with thermal and magnetic protection. • Pressure control valve • Water filter.

The simple and intuitive 24V control panel is complete with:

• ON/OFF switch • Function in-

dicator lights • Emergency stop button.

Electronic board, specially designed by Sirmac, allowing the following functions: intelligent and timed total stop (DTS/STT) with water shortage security; deactivation of all functions if the motor is stopped with closed gun for 60 minutes; power failure safety: the cleaner does not restart when the power is restored, but must be reset. On request, versions without intelligent total

stop (DBP/SBP) are available: machine stop after operating in bypass with closed spray-gun for an adjustable time during manufacturing





CUSTOMISED VERSIONS FOR ALL USE REQUIREMENTS

company has its own particular requirements which do not can be provided. always correspond to the standard models.

Sirmac designs and manufactures, on request, specific cleaners for all work requirements.

chassis that can be mounted on dedicated vehicles including the cleaner, a water tank available in both stainless steel and Both the skid and the mobile plastic, high or low pressure hose reels and a compartment fic hooks for lifting with a for housing accessories.

There are many different clea- For the use of the cleaner as a ning applications and each stationary unit, placed in a technical room, remote controls

There are also specific models for seawater supply with structure, pump and water circuit in AISI 316 stainless steel and models for hydro-blasting equipped with specific accesso-We design units on palletised ries for the required power and tanks containing calibrated

> version are available with specicrane.



ALIMENTATION À L'EAU **CHAUDE JUSQU'À 85°C**

Sur demande, certains modèles Vincent peuvent être équipés de pompes spécifiques pour l'alimentation en eau chaude et d'un système de sécurité pour contrôler la température de l'eau en entrée.







gh-pressure nozzle.

• Reel for 40m hose.

Standard accessories: • 15m Accessories for professional and indunon-staining high pressure hose. strial use, in compliance with safety re-• Spray-gun. • Lance. • Hi- gulations. The 15m high pressure hose allows cleaning without continuous displacement of the machine, always ke-On request: • Sand kit • Rota- eping the jet at a safe distance. On reting nozzle. • Reel for 20m hose. quest, we can supply longer hoses to facilitate cleaning of large structures.













SOME AREAS OF APPLICATION:

ships' hulls and fishing and paint . Graffiti reboats) · Motor vehicle moval · Power plants · production · Chemical Public works · Agriculindustry · Heavy indu- ture · Pipe cleaning · stry · Construction Rust removal · Cleasites (removal of ning of sieves, filters cement or concrete re- and tanks · Preparing sidues) · Metalworking surfaces for further · Stone working · Paper treatment · All kinds of production · Manu- surface removal. facture of petrochemicals • Transport • Mining industry · Cleaning of buildings . Re-

· Shipyards (cleaning of moval of incrustations



